

MINI CENTRIFUGE

TYPE 159



- * Small and compact centrifuge with rotor chamber in AISI 316 stainless steel.
- * Standard delivery includes external power supply.
- * Rotors of anodized aluminium. (Easy to autoclave).
- * Acceleration and braking 3 sec. total.
- * 7.200 rpm / 3.300 x g.
- * 3 years warranty.
- * Easy to place in air flow cabinets etc.
- * 8 different rotors (Easy to change)

TECHNICAL DATA:

Weight:	1,8 kg.
Dimensions 159.00 og 159.01:	Ø 153 x 150 mm.
Dimensions 159.02 og 159.03:	Ø 153 x 170 mm.
Dimension powersupply:	100 x 51 x 65 mm.
Rpm 159.00 and 159.02:	7.200 rpm
Rpm 159.01 and 159.03:	3.500 - 7.000 rpm
Operating temperature:	0-40°C
Main voltage centrifuge:	17 volt DC 15 watt.
External power supply:	230 volt AC.

ORDER INFORMATION:

159.00	Centrifuge complete incl. powersupply. (without rotor).
159.01	Same as model 159.00, with speed control. (3.500 - 7.000 rpm).
159.02	Same as model 159.00. extra high for "SPIN COLUMNS".
159.03	Same as model 159.02, with speed control. (3.500-7.000 rpm).
159.08.D	Rotor 8 x 1,5/2,0 ml. (3.300 x g).
159.18.P	Rotor 18 x 0,5 ml. (2.725 x g).
159.04.PCR	Rotor 4 x PCR strips. (1.970 x g).
159.15.DPCR	Rotor 2 PCR strips 4X1,5/2,0 ml (1.970 x g).
159.18.DP	Rotor 6 x 1,5 and 12 x 0,5 ml. (3.300 x g).
159.18.PCR	Rotor 18 x PCR 0,2 ml. (2.500 x g).
159.18.DPPCR	Rotor 6 x 1,5 ml, 6 x 0,5 ml og 6 x PCR. (2.500 x g).
159.18.DPCR	Rotor 6 x 1,5 ml and 12 x PCR. (2.500 x g).
159.06.01	Rotor 6 pcs "NUNC CRYO" vials Ø 13 x 41 mm 1,5 ml. (2.500 x g).

TAARNFALKEVEJ 18, DK-2650 HVIDOVRE, DENMARK
PHONE: +45 36 78 41 85 FAX: +45 36 78 64 65

OLE DICH APS